


P38 EVO 3-PHASE

	DIMENSIONS (Cm)	Effective 86 x 90 x h.85
		On Pallet 105 x 90 x h.91
	WEIGHT (Kg)	Effective 365
		On Pallet 375
	OIL	SAE = 40 Quantity = 8 lt.
	ELECTRIC MOTOR	400V - 50HZ 4 HP - 3 kW
RPM	9	

Bending capability	R. = 65 Kg. / mm ²			R. = 85 Kg. / mm ²		
	1 Ø 34	2 Ø 26	3 Ø 20	1 Ø 32	2 Ø 24	3 Ø 18

STANDARD EQUIPMENT

BIGGER ROTATING PLATE: DIMENSION Ø 395 mm:



It can support bushes up to Ø 220 mm to realize bending of big radius without need of extra equipments (Special Arm for large radii).



1 hardened square pin; 1 hardened stirrup bending pin;
3 hardened bush holding pins; 1 checking block; 1 pedal;
6 bushes Ø50-60-70-80-95-120mm; 1 set Allen keys .
2 Long Saddles, indispensable to realize the "double bend"!

OPTIONALS



"UNIQUE 2 in 1"
To bend more stirrups simultaneously and determine the length from the bending point.




Spirals/Hoops Device:
Allows to realize spiral/hoop armatures with bars Ø max.16 mm.



"Basic Angle Control" Panel:
Allows to set up manually 6 bending angles, that will be carried out in sequence.



"Angle Control" Panel:
This special computer permits to program up to 20 bending angles in very rapid and intuitive way.




2-Speed Motor:
Available on request for those who work bars of different diameters and want to optimize production times.



Special Bushes for large radii.



Working top "Type B": The cover in sheet metal prevents the turning plate from dust and material residuals.



Roller Bench:

To deposit and move the material. Available in different lengths, as needed.