

P42 3-PHASE

	DIMENSIONS (Cm)	Effective 105 x 95 x h.89
		On Pallet 105 x 95 x h.96
	WEIGHT (Kg)	Effective 490
		On Pallet 505
	OLIO	SAE = 40
		Quantity = 13 lt.
ELECTRIC MOTOR	400V - 50HZ 4 HP - 3 kW	
RPM	6	


Bending capability	R. = 65 Kg. / mm ²			R. = 85 Kg. / mm ²		
	1 Ø 36	2 Ø 28	3 Ø 22	1 Ø 34	2 Ø 26	3 Ø 20

STANDARD EQUIPMENT



1 hardened square pin; 1 hardened stirrup bending pin; 3 hardened bush holding pins; 1 checking block; 1 pedal; 6 bushes Ø50-60-70-80-95-120 mm; 1 set Allen keys .
2 Long Saddles, indispensable to realize the "double bend"!

OPTIONALS



"UNIQUE 2 in 1"
To bend more stirrups simultaneously and determine the length from the bending point.



Spirals/Hoops Device:
Allows to realize spiral/hoop armatures with bars Ø max.16 mm.




"Basic Angle Control" Panel:
Allows to set up manually 6 bending angles, that will be carried out in sequence.



"Angle Control" Panel:
This special computer permits to program up to 20 bending angles in very rapid and intuitive way.



2-Speed Motor:
Available on request for those who work bars of different diameters and want to optimize production times.



Special Arm and Bushes for large radii.



Working top "Type B": The cover in sheet metal prevents the turning plate from dust and material residuals.



Roller Bench:
To deposit and move the material. Available in different lengths, as needed.