

P52 3-PHASE

	DIMENSIONS (Cm)	<u>Effective</u> 105 x 95 x h.89
		<u>On Pallet</u> 105 x 95 x h.96
	WEIGHT (Kg)	<u>Effective</u> 575
		<u>On Pallet</u> 590
	OIL	SAE = 40
		Quantity = 13 lt.
ELECTRIC MOTOR	400V - 50HZ	
	5,5 HP - 4 kW	
RPM	6	

Bending capability	R. = 65 Kg. / mm²			R. = 85 Kg. / mm²		
	1 Ø 42	2 Ø 32	3 Ø 26	1 Ø 38	2 Ø 30	3 Ø 24

STANDARD EQUIPMENT



1 hardened square pin; 1 hardened stirrup bending pin; 3 hardened bush holding pins; 1 checking block; 1 pedal; 6 bushes Ø60-70-80-95-120-130 mm; 1 set Allen keys .

2 Long Saddles, indispensable to realize the "double bend"!

OPTIONALS



"UNIQUE 2 in 1"

To bend more stirrups simultaneously and determine the length from the bending point.



Spirals/Hoops Device:

Allows to realize spiral/hoop armatures with bars Ø max.16 mm.



"Basic Angle Control" Panel:

Allows to set up manually 6 bending angles, that will be carried out in sequence.




"Angle Control" Panel:

This special computer permits to program up to 20 bending angles in very rapid and intuitive way.



2-Speed Motor:

Available on request for those who work bars of different diameters and want to optimize production times.



Special Arm and Bushes for large radii.



Working top "Type B": The cover in sheet metal prevents the turning plate from dust and material residuals.



Roller Bench:

To deposit and move the material. Available in different lengths, as needed.