


## P55 3-PHASE



<b>DIMENSIONS (Cm)</b>	<b>Effective</b> 105 x 95 x h.89
	<b>On Pallet</b> 105 x 95 x h.96
<b>WEIGHT (Kg)</b>	<b>Effective</b> 620
	<b>On Pallet</b> 635
<b>OIL</b>	SAE = 40
	Quantity = 13 lt.
<b>ELECTRIC MOTOR</b>	400V - 50HZ
	7,5 HP - 5,5 kW
<b>RPM</b>	5,5








Bending capability	R. = 65 Kg. / mm <sup>2</sup>			R. = 85 Kg. / mm <sup>2</sup>		
	1 Ø 46	2 Ø 36	3 Ø 30	1 Ø 42	2 Ø 34	3 Ø 26

### STANDARD EQUIPMENT



1 hardened square pin; 1 hardened stirrup bending pin; 3 hardened bush holding pins; 1 checking block; 1 pedal; 6 bushes Ø60-70-80-95-120-130 mm; 1 set Allen keys .  
**4 Long Saddles, indispensable to realize the "double bend"!**

### OPTIONALS

 <p><b>"UNIQUE 2 in 1"</b> To bend more stirrups simultaneously and determine the length from the bending point.</p>	 <p><b>Spirals/Hoops Device:</b> Allows to realize spiral/hoop armatures with bars Ø max.16 mm.</p>	 <p><b>"Basic Angle Control" Panel:</b> Allows to set up manually 6 bending angles, that will be carried out in sequence.</p>	 <p><b>"Angle Control" Panel:</b> This special computer permits to program up to 20 bending angles in very rapid and intuitive way.</p>
 <p><b>2-Speed Motor:</b> Available on request for those who work bars of different diameters and want to optimize production times.</p>	 <p><b>Special Arm and Bushes for large radii.</b></p>	 <p><b>Working top "Type B":</b> The cover in sheet metal prevents the turning plate from dust and material residuals.</p>	



**Roller Bench:**  
To deposit and move the material. Available in different lengths, as needed.