


## PS16 A/C 3-PHASE

	<b>DIMENSIONS (Cm)</b>	<b>Effective</b> 82 x 90 x h.85
		<b>On Pallet</b> 105 x 80 x h.91/143
	<b>WEIGHT (Kg)</b>	<b>Effective</b> 280
		<b>On Pallet</b> 295
	<b>OIL</b>	SAE = 40
		Quantity = 5 lt.
<b>ELECTRIC MOTOR</b>	400V - 50HZ	
	2 HP - 1,5 kW	
<b>RPM</b>	18	

<b>Number of rods which may be bent simultaneously</b>	<b>R. = 65 Kg. / mm<sup>2</sup></b>					
	1 Ø 16	2 Ø 12	3 Ø 10	4 Ø 8	7 Ø 6	10 Ø 4

### STANDARD EQUIPMENT

#### STIRRUP LINEAR MEASURER



Device to measure the length of the bars for a flawless precision!

#### STIRRUP BENDING TOOL



Fixed on the working top



1 hardened square pin; 1 hardened stirrup bending pin; 3 hardened bush holding pins; 1 checking block; 1 pedal for remote control; 4 bushes Ø50-60-70-80mm; 1 set Allen keys.

#### "ANGLE CONTROL" PANEL



This special computer permits to program up to 20 bending angles in very rapid and intuitive way.

#### Examples of bending that can be realized:

